## NSN 5905-00-849-4322

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-849-4322

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.062 inches
Body Length:
1.250 inches
Body Width:
0.250 inches
Body Height:
0.359 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
9000.0
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal and unthreaded hole
Electrical Resistance Per Section:
50.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
9000.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+7.0 -55 degrees celsius single section and +0.0/+3.5 -25 degrees celsius single section and +0.0/+2.0 0 degrees celsius single section
and -2.5/+2.5 85 degrees celsius single section and +0.0/+5.5 125 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

0.25 free air single section

**Power Dissipation Rating Per Section In Watts:** 

125.0 single section

## NSN 5905-00-849-4322

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No