Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-849-4504

Section Quantity:

1

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.938 inches

Body Style:

Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 3 oclock and at 9 oclock

Nonturn Device Radius:

0.438 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

500.000 kilohms single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

NSN 5905-00-849-4504

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0