Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-849-6002

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.156 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

1.062 inches

## Mounting Bushing Length:

0.375 inches

#### Body Length:

## 0.625 inches

Shaft Style:

#### Round

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

312.0

## Nonturn Device Location:

At 9 oclock

## Nonturn Device Radius:

0.531 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

## **Terminal Location:**

Radially positioned over less than half the circumference

## **Mounting Method:**

Standard bushing

## **Electrical Resistance Per Section:**

1.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

312.0

## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

# NSN 5905-00-849-6002 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

2.25 free air single section

## **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

## Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A002a0