NSN 5905-00-849-6809



view Online at	nttps://aerobasegroup.com/nsn/5905-00-849-6809	
Section Quan	ty:	
1		
Body Style:		
Cylindrical bus	ing mounted	
Reliability Ind	cator:	
Not established		
Overall Lengt	:	
Between 1.203	inches and 1.297 inches	
Body Diamete	:	
Between 0.719	inches and 0.781 inches	
Shaft Diamete	:	
Between 0.124	inches and 0.126 inches	
Shaft Length:		
Between 0.844	inches and 0.906 inches	
Mounting Bus	ning Length:	
Between 0.359	inches and 0.391 inches	
Body Length:		
Between 0.359	inches and 0.391 inches	
Overall Diame	er:	
0.953 inches		
Shaft Style:		
Round, slotted		
Actuator Type		
Single shaft		
Maximum Sta	ing Torque:	
6.00 inch-ounc		

80.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.359 inches and 0.391 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

NSN 5905-00-849-6809

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 295.0 and 305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-94/2 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No