Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-849-6810

# Section Quantity: 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** Between 0.906 inches and 1.000 inches **Body Diameter:** Between 0.890 inches and 0.922 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: Between 0.469 inches and 0.531 inches **Body Length:** Between 0.437 inches and 0.469 inches **Overall Diameter:** 1.274 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** Between 0.422 inches and 0.454 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 7.5 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 251.0 and 318.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

# NSN 5905-00-849-6810

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



### Power Dissipation Rating Per Section In Watts:

1.0 free air single section

#### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

### Actuator Travel Control Feature:

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

#### Standard Taper Curve Per Section:

A single section

#### Test Data Document:

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

3 tab, solder lug

#### **Specification Data:**

81349-mil-r-94/4 government specification

Shelf Life:

N/a

Unit Of Measure:

## --

Demilitarization:

No

Fiig:

A002a0