## NSN 5905-00-849-7360

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-849-7360

Section Quantity:
1
Body Style:  Cylindrical bushing mounted
Cylindrical bushing mounted
Reliability Indicator:  Not established
Body Diameter: 0.938 inches
Shaft Diameter:
Between 0.109 inches and 0.141 inches
Shaft Length:  Between 0.859 inches and 0.891 inches
Mounting Bushing Length:
0.375 inches
Body Length: 0.469 inches
Shaft Style: Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Screw Thread Diameter: 0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
* * *
32.0 Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing  Electrical Resistance Per Section:
3.5 megohms single section
Rotary Actuator Travel In Angular Deg: 300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section  Power Dissipation Pating Per Section In Watter
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-30.0/+30.0 single section

## NSN 5905-00-849-7360

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
55.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: