Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-850-1487

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

1.3750 inches

Pilot Length:

0.0625 inches

Overall Length:

1.8705 inches

Undercut Diameter:

1.375 inches

Undercut Width:

0.0625 inches

Body Diameter:

1.750 inches

Shaft Diameter:

0.188 inches

Shaft Length:

0.558 inches

Body Length:

1.3125 inches

Mounting Lip Diameter:

1.7500 inches

Mounting Lip Depth:

0.0930 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

340.0

Maximum Running Torque:

3.00 inch-ounces

Shaft Runout:

0.001 inches

Terminal Location:

Radially positioned over less than half the circumference



Mounting Method:
Clamp ring
Electrical Resistance Per Section:
7.5 kilohms all sections
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 2nd section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 all sections
Power Dissipation Rating Per Section In Watts:
2.2 free air all sections
Function Conformity Per Section:
All sections independent linearity
Fixed Tap Quantity Per Section:
1 all sections
Tap Location Tolerance Per Section:
-1.0/+1.0 ohms all sections
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
3750.0 all sections
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Terminal Type And Quantity:
8 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0