## NSN 5905-00-850-1488

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-850-1488

Section Quantity:
2
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.750 inches
Shaft Diameter:
0.188 inches
Shaft Length:
0.563 inches
Body Length:
1.625 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Maximum Running Torque:
0.12 inch-ounces
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
7.5 ohms c and better finish
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.12/+0.12 1st section
Power Dissipation Rating Per Section In Watts:
2.2 free air all sections
Function Conformity Per Section:
All sections independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear

All sections linear

## NSN 5905-00-850-1488

No Fiig: A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Terminal Type And Quantity:
5 turret
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization: