NSN 5905-00-850-4677

-50.0/+50.0

30.100 ohms

Electrical Resistance:

Resistance Tolerance In Percent:

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-850-4677

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

| -1.000/+1.000 |
|--|
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 275.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+275.0 |
| Inclosure Method: |
| Encased |
| Terminal Type: |
| Tab, solder lug |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.438 inches |
| Body Length: |
| 1.062 inches |
| Body Width: |
| 0.531 inches |
| Body Height: |
| 0.562 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 0.719 inches |
| Power Dissipation Rating In Watts: |
| 8.000 free air |
| Mounting Hole Size: |
| 0.125 inches |
| Cubic Measure (non-core): |
| 0.317 cubic inches |
| Style Designator: |
| Axial terminal (s) |
| Test Data Document: |
| 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-r-18546/1 government specification |
| Shelf Life: |
| N/a |
| |

NSN 5905-00-850-4677

Inductive Wire Wound Fixed Resistor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A001a0