## NSN 5905-00-850-7210

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-850-7210

Electrical Resistance: 1,700 kilohms Resistance Tolerance In Percent: 5,000/+5,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25,0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25,0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25,0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55,0/4350,0 Inclosure Method:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: 5.0004-5.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 350.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/4-350.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Note established 30-04 Diameter: 0.469 inches 30-04 Length: 2.000 inches Power Dissipation Rating in Watts: 14.000 free air Style Designator: Avial terminal each end Fest Data Document: 31494-milrz64/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure:	-260.0/+260.0
Resistance Tolerance In Percent: 5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 25.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0/4-35.0 Inclosure Method: 25.0/4-35.0 Inclosure Method: 25.0/4-35.0 Inclosure Method: 26.00 26.0	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4-350.0 Inclosure Method: Encapsulated Terminal Type: Write lead Reliability Indicator: Not established 30dy Diameter:	4.700 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 350.0 Tempurature Range Of Tempurature	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  350.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+350.0  Inclosure Method:  incapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Baddy Diameter:  2,469 inches  Body Length:  2,000 inches  Power Dissipation Rating In Watts:  14.000 free air  Style Designator:  Availa terminal each end  Test Data Document:  31349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa Unit Of Measure:  - Demilitarization:  No	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  350.0  Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0+350.0  Inclosure Method: Encapsulated  Ferminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.469 inches  Body Length: 2.000 inches  Power Dissipation Rating In Watts: 14.000 free air  Style Designator: Axial terminal each end  Fest Data Document: 31349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Shelf Life: Wa  Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+350.0  nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 2.000 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: Wa Unit Of Measure: — Demilitarization: No	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+350.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Baddy Diameter:  10.469 inches  Boddy Length:  20.00 inches  Power Dissipation Rating In Watts:  14.000 free air  Style Designator:  Avail terminal each end  Test Data Document:  31349-miliz6/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format:  packuldes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:  No	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 2.000 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Fest Data Document: 31349-milize//4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure:	350.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 0.2000 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-mili26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure: Demilitarization: No	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.469 inches  Body Length:  2.000 inches  Power Dissipation Rating In Watts:  14.000 free air  Skyle Designator:  Axial terminal each end  Test Data Document:  31349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  V/a  Unit Of Measure:  Demilitarization:  No	-55.0/+350.0
Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.469 inches  Body Length:  2.000 inches  Power Dissipation Rating In Watts:  14.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  31349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.469 inches Body Length: 2.000 inches Power Dissipation Rating In Watts: 14.000 free air Style Designator: Axial terminal each end Fest Data Document: 31349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Encapsulated
Reliability Indicator:  Not established  Body Diameter:  0.469 inches  Body Length: 2.000 inches  Power Dissipation Rating In Watts: 14.000 free air  Style Designator: Axial terminal each end  Test Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Terminal Type:
Note stablished  Body Diameter:  0.469 inches  Body Length: 2.000 inches  Power Dissipation Rating In Watts:  14.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  B1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Wire lead
Body Diameter:  0.469 inches  Body Length: 2.000 inches  Power Dissipation Rating In Watts:  14.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Reliability Indicator:
Body Length:  2.000 inches  Power Dissipation Rating In Watts:  14.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Not established
Body Length: 2.000 inches  Power Dissipation Rating In Watts: 14.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Body Diameter:
2.000 inches  Power Dissipation Rating In Watts:  14.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  31349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	0.469 inches
Power Dissipation Rating In Watts:  14.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  31349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	Body Length:
Axial terminal each end  Test Data Document:  B1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	2.000 inches
Axial terminal each end  Test Data Document:  B1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  B1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	14.000 free air
Test Data Document:  81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Style Designator:
B1349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	81349-milr26/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a Unit Of Measure: Demilitarization:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
V/a Unit Of Measure:  Demilitarization:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization:	Shelf Life:
Demilitarization:	N/a
No	Unit Of Measure:
No	<del></del>
	Demilitarization:
Fiig:	No
	Fiig:
A001a0	A001a0