NSN 5905-00-850-8493

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-850-8493

Section Quantity:
1

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.282 inches **Terminal Length:** Between 5.875 inches and 6.000 inches **Overall Height:** 0.312 inches **Overall Width:** 0.266 inches **Mounting Hole Diameter:** 0.086 inches **Shaft Diameter:** 0.115 inches **Shaft Length:** 0.032 inches **Body Length:** 1.250 inches **Body Width:** 0.250 inches **Body Height:** 0.312 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Maximum Starting Torque:** 8.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:**

Terminal Location:

2

Mounting Method:

Unthreaded hole

Rear end

NSN 5905-00-850-8493

Precision Wire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
2.500 kilohms single section
Rotary Actuator Travel In Angular Deg:
7920.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power
165.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A002a0