Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-850-8891

Section Quantity:

1

Body Style:

Cylindrical hole/slot mounted

Reliability Indicator:

Not established

Overall Length:

5.000 inches

First Flat Length:

1.562 inches

Flat Height:

0.344 inches

Body Diameter:

12.000 inches

Shaft Diameter:

0.375 inches

Shaft Length:

2.000 inches

Body Length:

3.000 inches

Overall Diameter:

12.375 inches

Mounting Hole/stud Circle Diameter:

6.375 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

335.0

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

20.0

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

NSN 5905-00-850-8891

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
16.0 ohms single section
Rotary Actuator Travel In Angular Deg:
335.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
300.0 single section
Power Dissipation Rating Per Section In Watts:
1000.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0