

View Online at https://aerobasegroup.com/nsn/5905-00-850-9483

Section Quantity: 1 Body Style: Cylindrical bushing mounted Reliability Indicator:

Not established

Overall Length:

Between 1.776 inches and 1.848 inches

Body Diameter:

Between 0.859 inches and 0.891 inches

Shaft Diameter:

0.250 inches

Shaft Length:

Between 0.796 inches and 0.828 inches

Mounting Bushing Length:

Between 0.296 inches and 0.328 inches

Body Length:

Between 0.980 inches and 1.020 inches

Overall Diameter:

1.063 inches

Shaft Style:

Round, slotted

Contact Arm Electrical Off Position:

Fully ccw-cw

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 3600.0 and 3610.0

Maximum Starting Torque:

0.60 inch-ounces

Maximum Stop Torque:

48.00 inch-ounces

Nonturn Device Location:

At 7 oclock

Nonturn Device Radius:

Between 0.280 inches and 0.300 inches

Shaft End Play:

0.005 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.005 inches



Pilot Dia	ameter Runout:
0.002 ind	ches
Shaft Ra	adial Play:
0.003 ind	ches
Mechan	ical Backlash In Deg Angular Rotation:
1.0	
Screw T	Thread Diameter:
0.375 ind	ches
Screw T	Thread Series Designator:
Unef	
Screw T	hready Qty Per Inch (tpi):
32.0	
Termina	al Location:
Radially	positioned over less than half the circumference
Mountin	ng Method:
Standard	d bushing w/shaft seal
Electrica	al Resistance Per Section:
30.0 kilo	hms single section
Rotary A	Actuator Travel In Angular Deg:
Between	n 3600.0 and 3610.0
Functio	n Conformity Tolerance Per Section:
-0.20/+0	.20 single section
Ambien	t Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 sir	ngle section
Power D	Dissipation Rating Per Section In Watts:
2.0 free	air single section
Functio	n Conformity Per Section:
Single se	ection independent linearity
Resista	nce Tolerance Per Section In Percent:
-3.0/+3.0) single section
Actuato	r Travel Control Feature:
Stops	
Functio	n Characteristic Per Section:
Single se	ection linear
Tempura	ature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+2	0.0 single section
Ambien	t Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 sing	gle section
Termina	al Type And Quantity:
3 tab, so	older lug
Shelf Lif	fe:
N/a	
Unit Of	Measure

Unit Of Measure:



Demilitarization:

No

Fiig:

A002a0