Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-850-9500

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** Between 1.254 inches and 1.358 inches **Terminal Length:** Between 0.469 inches and 0.624 inches **Overall Height:** 0.998 inches **Overall Width:** Between 0.235 inches and 0.300 inches **Mounting Hole Diameter:** Between 0.088 inches and 0.098 inches Shaft Diameter: Between 0.036 inches and 0.077 inches Shaft Length: Between 0.100 inches and 0.140 inches **Body Length:** Between 1.218 inches and 1.281 inches **Body Width:** Between 0.235 inches and 0.300 inches **Body Height:** Between 0.280 inches and 0.374 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 6120.0 and 9720.0 Maximum Starting Torque: 8.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.680 inches and 0.720 inches Lateral Distance Between Mounting Hole Centers: Between 0.995 inches and 1.005 inches **Mounting Facility Quantity:** 2 **Terminal Location:** 

Lower adjacent side from adjustment control

## NSN 5905-00-850-9500

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Unthreaded holes and pins
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
200.000 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 6120.0 and 9720.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.290 inches and 0.310 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0/+200.0 single section
Power Dissipation Rating Per Section In Watts:
0.8 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0