

View Online at https://aerobasegroup.com/nsn/5905-00-851-0356

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Overall Length:**

2.905 inches

#### **Body Diameter:**

1.844 inches

Shaft Diameter:

Between 0.249 inches and 0.250 inches

#### Shaft Length:

Between 0.781 inches and 0.843 inches

## Mounting Bushing Length:

0.312 inches

## **Body Length:**

2.062 inches

## **Overall Diameter:**

2.500 inches

## Shaft Style:

Round

#### Shaft Bearing Type:

Sleeve

## Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

3600.0

## Maximum Starting Torque:

3.00 inch-ounces

## Maximum Running Torque:

3.00 inch-ounces

#### Maximum Stop Torque:

550.00 inch-ounces

## **Nonturn Device Location:**

At 6 oclock

# Nonturn Device Radius:

0.562 inches

# Shaft End Play:

0.005 inches

## Shaft Runout:

0.005 inches



# Lateral Runout: 0.003 inches **Pilot Diameter Runout:** 0.002 inches **Shaft Radial Play:** 0.004 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Standard bushing **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 50.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.05/+0.05 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -1.0/+1.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0