NSN 5905-00-851-2402

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-851-2402 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** Between 0.172 inches and 0.202 inches **Mounting Hole Diameter:** 0.075 inches **Shaft Diameter:** Between 0.055 inches and 0.060 inches **Shaft Length:** 0.030 inches **Body Length:** Between 0.495 inches and 0.505 inches **Body Width:** Between 0.495 inches and 0.505 inches **Body Height:** Between 0.210 inches and 0.230 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.195 inches and 0.205 inches **Fragility Factor:** Moderately rugged **Mounting Facility Quantity:** 2 **Terminal Location:** Left adjacent side two rows

Mounting Method:

Unthreaded hole

NSN 5905-00-851-2402

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Terminal Rows:
Between 0.095 inches and 0.105 inches
Features Provided:
Hermetically sealed
Cubic Measure:
0.054 cubic inches
Electrical Resistance Per Section:
50.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.095 mils and 0.105 centimeters
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 7th secondary quality
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A002a0