

View Online at <https://aerobasegroup.com/nsn/5905-00-851-2866>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 1.3120 inches and 1.3125 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

1.625 inches

**Undercut Diameter:**

Between 1.3120 inches and 1.3125 inches

**Undercut Width:**

0.06200 inches

**Body Diameter:**

1.438 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.375 inches

**Body Length:**

1.250 inches

**Overall Diameter:**

1.672 inches

**Mounting Lip Diameter:**

1.4370 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Maximum Starting Torque:**

0.50 inch-ounces

**Shaft Runout:**

0.004 inches

**Pilot Diameter Runout:**

0.001 inches

**Shaft Radial Play:**

0.001 inches

**Terminal Location:**

Radially positioned over more than half the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

24.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

130.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Fixed Tap Quantity Per Section:**

24 single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

80.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

25 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0