NSN 5905-00-851-2879

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-851-2879 **Section Quantity: Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 2.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.15/+0.15 single section **Power Dissipation Rating Per Section In Watts:** 2.5 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -1.0/+1.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure:**

Demilitarization:No

NSN 5905-00-851-2879

Precision Wire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0