NSN 5905-00-851-4898

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-851-4898 **Section Quantity: Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Shaft Style:** Round, slotted Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.530 inches **Switch Operating Position:** Start of rotation **Switch Contact Arrangement:** Single pole, double throw, three positions maintained **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): **Mounting Method:** Standard bushing **Features Provided:** Switch

Electrical Resistance Per Section:

20.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

NSN 5905-00-851-4898

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Switch Current Type And Rating In Amps:
3.000 ac/dc
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0