NSN 5905-00-851-8212

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-851-8212 **Section Quantity:** 3 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 2.500 inches **Undercut Diameter:** 0.750 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.1248 inches and 0.125 inches **Shaft Length:** 0.375 inches **Body Length:** 1.750 inches **Overall Diameter:** 1.376 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 354.0 **Maximum Starting Torque:**

0.45 inch-ouncesMaximum Running Torque:0.45 inch-ounces

NSN 5905-00-851-8212

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft End Play:
0.002 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.003 inches
Fragility Factor:
Moderately delicate
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.0 percent, rated amperes c and better select
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 2nd section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
90.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-35.0/+35.0 2nd section
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary finish
Function Conformity Per Section:
3rd section zero based linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 all sections
Unpackaged Unit Weight:
1.50 ounces
Terminal Type And Quantity:
9 tab, solder lug
Shelf Life:

N/a

NSN 5905-00-851-8212

Precision Wire Wound Variable Resistor - Page 3 of 3



			ure:	

--

Demilitarization:

No

Fiig:

A002a0