NSN 5905-00-851-8488

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-851-8488 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Terminal Length:** 0.500 inches **Mounting Hole Diameter:** 0.078 inches **Shaft Diameter:** 0.075 inches **Shaft Length:** 0.035 inches **Body Length:** 0.500 inches **Body Width:** 0.188 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Center To Center Distance Between Terminals:** 0.200 inches **Lateral Distance Between Mounting Hole Centers:** 0.520 inches **Mounting Facility Quantity: Terminal Location:** Lower adjacent side two rows **Mounting Method:** Unthreaded hole **Center To Center Distance Between Terminal Rows:** 0.100 inches **Features Provided:**

Humidity proof

Electrical Resistance Per Section:

50.0 ohms single section

NSN 5905-00-851-8488

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
0.000
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power
75.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
.0 free air single section
Resistance Tolerance Per Section In Percent:
5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Ferminal Type And Quantity:
B pin
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A002a0