## NSN 5905-00-852-2005

**Fiig:** A001a0

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-852-2005

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -260.0/+260.0 Electrical Resistance: 240.000 ohms Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: -Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches Body Diameter: 1.312 inches Body Length: 4.000 inches Power Dissipation Rating In Watts: -78.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-milt-26 specification (includes engineering type bulletins, brochures, etc., that teflect specification type data in specification format; excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental
Electrical Resistance: 240.000 ohms Resistance Tolerance In Percent: -5.000/45.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab. solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches Body Diameter: 1.312 inches Body Diameter: 1.312 inches Power Dissipation Rating In Watts: 78.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil+-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.663 inches Body Diameter: 1.312 inches Body Length: 4.000 inches Power Dissipation Rating In Watts: 78.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches Body Diameter: 1.312 inches Body Diameter: 1.312 inches Body Length: 4.000 inches Power Dissipation Rating In Watts: 78.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format:
-5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches Body Diameter: 1.312 inches Body Length: 4.000 inches Power Dissipation Rating In Watts: 78.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -56.0/+350.0  Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches Body Diameter: 1.312 inches Body Length: 4.000 inches Power Dissipation Rating In Watts: Teminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.5(4)-4350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches Body Diameter: 1.312 inches Body Diameter: 1.312 inches Body Length: 4.000 inches Power Dissipation Rating In Watts: Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0  Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches Body Diameter: 1.312 inches Body Diameter: 4.000 inches Power Dissipation Rating In Watts: 78.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches Body Diameter: 1.312 inches Body Length: 4.000 inches Power Dissipation Rating In Watts: 78.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches Body Diameter: 1.312 inches Body Length: 4.000 inches Power Dissipation Rating In Watts: 78.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
-55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches Body Diameter: 1.312 inches Body Length: 4.000 inches Power Dissipation Rating In Watts: 78.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches Body Diameter: 1.312 inches Body Length: 4.000 inches Power Dissipation Rating In Watts: 78.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Encapsulated  Terminal Type: Tab, solder lug  Reliability Indicator: Not established  Terminal Length: 0.563 inches  Body Diameter: 1.312 inches  Body Length: 4.000 inches  Power Dissipation Rating In Watts: 78.000 free air  Terminal Width: 0.328 inches  Style Designator: Radial terminal each end  Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Terminal Type: Tab, solder lug  Reliability Indicator: Not established  Terminal Length: 0.563 inches  Body Diameter: 1.312 inches  Body Length: 4.000 inches  Power Dissipation Rating In Watts: 78.000 free air  Terminal Width: 0.328 inches  Style Designator: Radial terminal each end  Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Tab, solder lug  Reliability Indicator:  Not established  Terminal Length: 0.563 inches  Body Diameter: 1.312 inches  Body Length: 4.000 inches  Power Dissipation Rating In Watts: 78.000 free air  Terminal Width: 0.328 inches  Style Designator:  Radial terminal each end  Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Reliability Indicator: Not established  Terminal Length: 0.563 inches  Body Diameter: 1.312 inches  Body Length: 4.000 inches  Power Dissipation Rating In Watts: 78.000 free air  Terminal Width: 0.328 inches  Style Designator: Radial terminal each end  Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Not established  Terminal Length: 0.563 inches  Body Diameter: 1.312 inches  Body Length: 4.000 inches  Power Dissipation Rating In Watts: 78.000 free air  Terminal Width: 0.328 inches  Style Designator: Radial terminal each end  Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Terminal Length:  0.563 inches  Body Diameter:  1.312 inches  Body Length:  4.000 inches  Power Dissipation Rating In Watts:  78.000 free air  Terminal Width:  0.328 inches  Style Designator:  Radial terminal each end  Test Data Document:  81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
0.563 inches  Body Diameter:  1.312 inches  Body Length:  4.000 inches  Power Dissipation Rating In Watts:  78.000 free air  Terminal Width:  0.328 inches  Style Designator:  Radial terminal each end  Test Data Document:  81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Body Diameter:  1.312 inches  Body Length:  4.000 inches  Power Dissipation Rating In Watts:  78.000 free air  Terminal Width:  0.328 inches  Style Designator:  Radial terminal each end  Test Data Document:  81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
1.312 inches  Body Length: 4.000 inches  Power Dissipation Rating In Watts: 78.000 free air  Terminal Width: 0.328 inches  Style Designator: Radial terminal each end  Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Body Length: 4.000 inches  Power Dissipation Rating In Watts: 78.000 free air  Terminal Width: 0.328 inches  Style Designator: Radial terminal each end  Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
4.000 inches  Power Dissipation Rating In Watts:  78.000 free air  Terminal Width:  0.328 inches  Style Designator:  Radial terminal each end  Test Data Document:  81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Power Dissipation Rating In Watts: 78.000 free air Terminal Width: 0.328 inches Style Designator: Radial terminal each end Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
78.000 free air  Terminal Width:  0.328 inches  Style Designator:  Radial terminal each end  Test Data Document:  81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Terminal Width:  0.328 inches  Style Designator:  Radial terminal each end  Test Data Document:  81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
0.328 inches  Style Designator:  Radial terminal each end  Test Data Document:  81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Style Designator:  Radial terminal each end  Test Data Document:  81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Radial terminal each end  Test Data Document:  81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Test Data Document: 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-26/3 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No