## NSN 5905-00-852-9278

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-852-9278

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.313 inches
Body Diameter:
0.875 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.688 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Nonturn Device Location:
Nonturn Device Location: At 6 oclock
At 6 oclock
At 6 oclock  Nonturn Device Radius:
At 6 oclock  Nonturn Device Radius:  0.250 inches
At 6 oclock  Nonturn Device Radius:  0.250 inches  Screw Thread Diameter:
At 6 oclock  Nonturn Device Radius:  0.250 inches  Screw Thread Diameter:  0.250 inches
At 6 oclock  Nonturn Device Radius:  0.250 inches  Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator:
At 6 oclock  Nonturn Device Radius:  0.250 inches  Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator:  Unef
At 6 oclock  Nonturn Device Radius: 0.250 inches  Screw Thread Diameter: 0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi):
At 6 oclock  Nonturn Device Radius:  0.250 inches  Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0
At 6 oclock  Nonturn Device Radius:  0.250 inches  Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:
At 6 oclock  Nonturn Device Radius:  0.250 inches  Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Radially positioned over less than half the circumference  Mounting Method:
At 6 oclock  Nonturn Device Radius:  0.250 inches  Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference
At 6 oclock  Nonturn Device Radius:  0.250 inches  Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference  Mounting Method:  Standard bushing  Electrical Resistance Per Section:
At 6 oclock  Nonturn Device Radius:  0.250 inches  Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator: Unef  Screw Thready Qty Per Inch (tpi): 32.0  Terminal Location: Radially positioned over less than half the circumference  Mounting Method: Standard bushing  Electrical Resistance Per Section: 125.000 ohms single section
At 6 oclock  Nonturn Device Radius:  0.250 inches  Screw Thread Diameter:  0.250 inches  Screw Thread Series Designator:  Unef  Screw Thready Qty Per Inch (tpi):  32.0  Terminal Location:  Radially positioned over less than half the circumference  Mounting Method:  Standard bushing  Electrical Resistance Per Section:

-10.0/+10.0 single section

## NSN 5905-00-852-9278

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



<b>Standard Taper Curve Per Section:</b>
A single section
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0