NSN 5905-00-852-9741

Fiig: A001a0

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-852-9741

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -260.0/+260.0 Electrical Resistance: 8.200 kilohms Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches |
|--|
| Electrical Resistance: 8,200 kilohms Resistance Tolerance In Percent: -5,000/+5,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25,0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350,0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55,0/+350,0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0,563 inches |
| 8.200 kilohms Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches |
| Resistance Tolerance In Percent: -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches |
| -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches |
| 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches |
| 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches |
| -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches |
| Inclosure Method: Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches |
| Encapsulated Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches |
| Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches |
| Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.563 inches |
| Reliability Indicator: Not established Terminal Length: 0.563 inches |
| Not established Terminal Length: 0.563 inches |
| Terminal Length: 0.563 inches |
| 0.563 inches |
| |
| Pady Diameters |
| Body Diameter: |
| 1.312 inches |
| Body Length: |
| 10.500 inches |
| Power Dissipation Rating In Watts: |
| 210.000 free air |
| Terminal Width: |
| 0.328 inches |
| Style Designator: |
| Radial terminal each end |
| Test Data Document: |
| 81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-r-26/3 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |