Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-853-0092

Section	Quantity:

1

**Reliability Indicator:** 

Not established

# Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

#### Mounting Bushing Length:

0.375 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Nonturn Device Location:

At 9 oclock

#### Nonturn Device Radius:

0.531 inches

## Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

#### **Mounting Method:**

Standard bushing

## **Electrical Resistance Per Section:**

1.0 megohms single section

## **Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

## Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5905-00-853-0092

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

Fiig: A002a0

