NSN 5905-00-853-3916

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-853-3916

Electrical Resistance: 16.000 ohms Resistance Tolerance In Percent: 5.0004-5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 35.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4350.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 0.662 inches 3040 Diameter: 1.062 inches 3040 Poimeter: 3040 Poimeter: 3050 Poi	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 5.000/4-5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0-4350.0 Refound Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0-4350.0 Refound Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0-4350.0 Refound Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0-25.0-25.0-25.0-25.0-25.0-25.0-25.0-	-400.0/+400.0
Resistance Tolerance in Percent: 5.000/45.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 25.0 26.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 25.0 25.0 25.0 25.0 25.0 25.0 25.0	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Tempurature Range Of Te	16.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0.4350.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 25.02 inches 25.04 Jameter: 25.02 inches 25.04 Jameter: 25.05 part of the Second Power Second Po	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Immurature Range Of Tempurature Coefficient In Deg Celsius: 55.0.4°350.0 Inclosure Method: Incapsulated Immurature In Type: Immurature In Type: Immurature In Type: Immurature In Immurature	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 1.562 inches 30dy Diameter: 1.162 inches 30dy Length: 4.188 inches Power Dissipation Rating In Watts: 72.000 free air Skyle Designator: Avail terminal each end Tests Data Document: 31349-milit26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Unit Of Measure: - Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 nclosure Method: Encapsulated Ferminal Type: Ferrule Ferminal Length: 0.562 inches Body Diameter: 1.062 inches Body Diameter: 1.062 inches Body Length: 4.188 inches Power Dissipation Rating In Watts: 77.2.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Duitt Of Measure: Demilitarization: No Filig:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 1.562 inches Body Diameter: 1.062 inches Body Length: 1.188 inches Power Dissipation Rating In Watts: 72.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: - Demilitarization: No Filig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
inclosure Method: Encapsulated Ferminal Type: Ferrule Ferminal Length: 0.562 inches Body Diameter: 1.062 inches Body Length: 4.188 inches Power Dissipation Rating In Watts: 72.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milit26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization: No Filig:	350.0
Inclosure Method: Encapsulated Ferminal Type: Ferrule Ferminal Length: 10.562 inches Body Diameter: 10.602 inches Body Length: 14.188 inches Power Dissipation Rating In Watts: 72.000 free air Style Designator: Axial terminal each end Fest Data Document: 131349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure: Demilitarization: No Filig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Ferrule Ferrule Ferminal Length: 0.562 inches Body Diameter: 1.062 inches Body Diameter: 1.062 inches Body Length: 1.188 inches Power Dissipation Rating In Watts: 72.000 free air Style Designator: Avial terminal each end Fest Data Document: 31349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: V/a Unit Of Measure: Demilitarization: No Fiig:	-55.0/+350.0
Ferrule Ferrule Ferrula Ferrula Ferrula Ferrula Ferrula Ferrula Ferrula Ferrula Ferrula Ferrula Ferrula Ferr	Inclosure Method:
Ferrule Ferrinal Length: 0.562 inches Body Diameter: 1.062 inches Body Length: 4.188 inches Power Dissipation Rating In Watts: 72.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Encapsulated
Terminal Length: 0.562 inches Body Diameter: 1.062 inches Body Length: 4.188 inches Power Dissipation Rating In Watts: 72.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill/26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Terminal Type:
Body Diameter: 1. 062 inches Body Length: 4. 188 inches Power Dissipation Rating In Watts: 7. 2. 000 free air Style Designator: Axial terminal each end Fest Data Document: 8. 13.49-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Ferrule
Body Length: 1.062 inches Body Length: 4.188 inches Power Dissipation Rating In Watts: 7/2.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Terminal Length:
1.062 inches Body Length: 4.188 inches Power Dissipation Rating In Watts: 72.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Unit Of Measure: Demilitarization: No Filg:	0.562 inches
Body Length: 4.188 inches Power Dissipation Rating In Watts: 72.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization: No Filg:	Body Diameter:
4.188 inches Power Dissipation Rating In Watts: 72.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.062 inches
Power Dissipation Rating In Watts: 72.000 free air Style Designator: Axial terminal each end Test Data Document: 31349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
Style Designator: Axial terminal each end Test Data Document: B1349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	4.188 inches
Style Designator: Axial terminal each end Test Data Document: 31349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	72.000 free air
Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
B1349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Unit Of Measure: Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Filig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
\001a0	Fiig:
100 100	A001a0