

View Online at <https://aerobasegroup.com/nsn/5905-00-853-6034>

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Terminal Length:

0.500 inches

Mounting Hole Diameter:

0.086 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.188 inches

Body Length:

1.340 inches

Body Width:

0.300 inches

Body Height:

0.360 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Center To Center Distance Between Terminals:

0.700 inches

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal and unthreaded hole

Center To Center Distance Between Terminal Rows:

0.100 inches

Features Provided:

Humidity proof

Electrical Resistance Per Section:

10.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

9000.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.300 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

135.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.8 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0