Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-853-6651

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### **Reliability Indicator:**

Not established

### **Overall Length:**

1.250 inches

#### **Body Diameter:**

1.156 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

#### Mounting Bushing Length:

### 0.500 inches

**Body Length:** 

0.625 inches

#### **Overall Diameter:**

1.453 inches

### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Nonturn Device Location:

At 9 oclock

#### **Nonturn Device Radius:**

0.531 inches

#### Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Locking bushing

# **Electrical Resistance Per Section:**

250.000 ohms single section

# Power Dissipation Rating Per Section In Watts:

2.0 free air single section



**Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Standard Taper Curve Per Section: A single section Terminal Type And Quantity: 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A002a0