Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-854-2549

Section Quantity:

2

Reliability Indicator:

Not established

Shaft Diameter:

0.250 inches

Shaft Length:

1.875 inches

Mounting Bushing Length:

0.375 inches

Overall Diameter:

1.156 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

10.000 percent, rated amperes c and better industrial clears

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 2nd section

Standard Taper Curve Per Section:

A single section

Special Features:

Shaft drilled w/0.063 in. Diameter hole spaced 0.500 in. Frommtg surface

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

NSN 5905-00-854-2549

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0