NSN 5905-00-854-9290

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-854-9290 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.812 inches **Body Diameter:** 1.812 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** Between 0.781 inches and 0.844 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** 2.000 inches **Overall Diameter:** 2.156 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Maximum Stop Torque:** 550.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:**

0.562 inches **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.0005 inches **Lateral Runout:** 0.003 inches

NSN 5905-00-854-9290

Precision Wire Wound Variable Resistor - Page 2 of 3



Pilot Diameter Runout: 0.002 inches **Shaft Radial Play:** 0.003 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Standard bushing **Features Provided:** Nonmetallic shaft **Electrical Resistance Per Section:** 10.0 kilohms single section Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation: 1800.0 single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.25/+0.25 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Fixed Tap Quantity Per Section:** 1 single section **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Continuous motion **Tap Location From Ccw Terminal Per Section In Ohms:** 5000.0 single section **Function Characteristic Per Section:** Single section linear

-0.0/+130.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

40.0 single section

NSN 5905-00-854-9290

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal	Type	And	Quantity:
----------	------	-----	-----------

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0