

View Online at <https://aerobasegroup.com/nsn/5905-00-855-0090>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.891 inches

First Flat Length:

Between 0.063 inches and 0.073 inches

Flat Height:

Between 0.042 inches and 0.052 inches

Body Diameter:

Between 0.248 inches and 0.250 inches

Shaft Diameter:

1.156 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.500 inches

Body Length:

1.266 inches

Overall Diameter:

1.484 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

250.000 percent, rated amperes c and better industrial clears

Power Dissipation Rating Per Section In Watts:

2.0 free air single section and 1.8 heat sink single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 2nd section

Standard Taper Curve Per Section:

A single section

Special Features:

0.500 in. Long bushing

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0