NSN 5905-00-855-1344

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-855-1344

| Electrical Resistance: 11.800 kilohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 Inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end |
|--|
| Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: -Encapsulated Terminal Type: |
| Resistance Tolerance In Percent: 1.1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.250 inches Body Length: 10.750 inches Power Dissipation Rating In Watts: 10.500 free air Style Designator: |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: 15.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| Body Length: 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| 0.750 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| Power Dissipation Rating In Watts: 0.500 free air Style Designator: |
| 0.500 free air Style Designator: |
| Style Designator: |
| |
| Axial terminal each end |
| |
| Test Data Document: |
| 31349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 31349-mil-r-10509/3 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A001a0 |