## NSN 5905-00-855-2311

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-855-2311

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Shaft Diameter:
0.100 inches
Shaft Length:
0.020 inches
Mounting Stud Length:
0.156 inches
Body Length:
0.355 inches
Body Width:
0.250 inches
Body Height:
0.250 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Lateral Distance Between Mounting Hole Centers:
0.300 inches
Screw Thread Diameter:
0.060 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
80.0
Mounting Facility Quantity:
2
Terminal Location:
Rear end
Mounting Method:
Threaded stud
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:

360.0

## NSN 5905-00-855-2311

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: