## NSN 5905-00-855-3631

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-855-3631 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.750 inches **Shaft Diameter:** 0.250 inches

**Mounting Bushing Length:** 

0.500 inches

**Shaft Length:** 0.625 inches

**Body Length:** 

1.000 inches

**Shaft Style:** 

Round, slotted

**Actuator Type:** 

Single shaft

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Locking bushing

**Electrical Resistance Per Section:** 

3.0 kilohms single section

**Power Dissipation Rating Per Section In Watts:** 

4.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

## NSN 5905-00-855-3631

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0