NSN 5905-00-855-4432

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-855-4432

Electrical Resistance: 10.000 kilohms Resistance Tolerance In Percent: 1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Resistance Tolerance In Percent: 1.1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Resistance Tolerance In Percent: 1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 175.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.250 inches Body Length: 10.750 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.250 inches Body Length: 10.750 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0 to 175.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
55.0 to 175.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Not established Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Body Diameter: 0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
0.250 inches Body Length: 0.750 inches Power Dissipation Rating In Watts:
Body Length: 0.750 inches Power Dissipation Rating In Watts:
0.750 inches Power Dissipation Rating In Watts:
Power Dissipation Rating In Watts:
) 500 from air
7.500 free all
Style Designator:
Axial terminal each end
Test Data Document:
31349-mil-r-10509 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-10509/3 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A001a0