NSN 5905-00-855-6131

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-855-6131

Electrical Resistance: 39,000 ohms Resistance Tolerance In Percent: 45,000/45,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25,0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350,0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 45,000/45,000 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 5,052 inches Body Diameter: 5,0750 inches Body Length: 1,438 inches Power Dissipation Rating In Watts: 20,000 free air Style Designator: Axial terminal each end Test Data Document: 81349-miliz26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: No Demilitarization: No Filig:	
Electrical Resistance: 39 000 ohms Resistance Tolerance In Percent: 5-5000/4-5000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25-0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 35-0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350-0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/4-350.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 0.562 inches Body Diamoter: 0.750 inches Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-miliz8/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: No Publificatization: No Filig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -5.000/4-5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: -25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: -25.0 (A.350.0) Inclosure Method: -25.0 (A.350.0) Inclosure M	-260.0/+260.0
Resistance Tolerance in Percent: -5.000/+5.000 Ambient Tempurature in Deg Celsius At Full Rated Power: -5.00 -5.00 -6.000	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: -0.562 inches Body Diameter: -0.750 inches Body Length: -1.438 inches Power Dissipation Rating In Watts: -0.000 free air Style Designator:	39.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 35.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: -0.562 inches Body Diameter: -0.750 inches Body Diameter: -0.750 inches Power Dissipation Rating In Watts: -20.000 free air Style Designator:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 0.562 inches Body Diameter: 0.750 inches Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr28/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	-5.000/+5.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 0.562 inches Body Diameter: 0.750 inches Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Tests Data Document: 81349-milit26/f specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.): Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 0.562 inches Body Diameter: 0.750 inches Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr/26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+350.0 Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 10.562 inches Body Diameter: 10.750 inches Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.0000 free air Style Designator: Axial terminal each end Test Data Document: 81349-millr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 0.562 inches Body Diameter: 0.750 inches Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milit26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	350.0
Inclosure Method: Encapsulated Terminal Type: Ferrule Terminal Length: 0.562 inches Body Diameter: 0.750 inches Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Ferrule Terminal Length: 0.562 inches Body Diameter: 0.750 inches Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	-55.0/+350.0
Terminal Type: Ferrule Terminal Length: 0.562 inches Body Diameter: 0.750 inches Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Inclosure Method:
Ferrule Terminal Length: 0.562 inches Body Diameter: 0.750 inches Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Encapsulated
Terminal Length: 0.562 inches Body Diameter: 0.750 inches Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type:
Body Diameter: 0.750 inches Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ferrule
Body Diameter: 0.750 inches Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Length:
Double 1.438 inches Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.562 inches
Body Length: 1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
1.438 inches Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.750 inches
Power Dissipation Rating In Watts: 20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
20.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.438 inches
Style Designator: Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	20.000 free air
Test Data Document: 81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-milr26/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Unit Of Measure: Demilitarization: No Filig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0