## NSN 5905-00-855-8971

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



/nsn/5905-00-855-8971

View Online at https://aerobasegroup.com/
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
Between 3.781 inches and 3.843 inches
First Flat Length:
Between 0.433 inches and 0.443 inches
Flat Height:
Between 0.213 inches and 0.223 inches
Body Diameter:
Between 1.781 inches and 1.843 inches
Shaft Diameter:
Between 0.2494 inches and 0.2497 inches
Shaft Length:
Between 0.807 inches and 0.817 inches
Mounting Bushing Length:
Between 0.291 inches and 0.343 inches
Body Length:
Between 1.969 inches and 2.031 inches
Overall Diameter:
Between 2.125 inches and 2.187 inches
Shaft Style:
Round, flatted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Maximum Starting Torque:
2.00 inch-ounces
Maximum Running Torque:
1.50 inch-ounces
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
Between 0.531 inches and 0.593 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:

Unef

## NSN 5905-00-855-8971

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
300.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3604.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A002a0