## NSN 5905-00-856-1585

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-856-1585

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
1.8750 inches
Pilot Length:
Between 0.0570 inches and 0.0670 inches
Overall Length:
1.656 inches
Undercut Diameter:
1.850 inches
Undercut Width:
0.0730 inches
Body Diameter:
1.875 inches
Shaft Diameter:
Between 0.249 inches and 0.250 inches
Shaft Length:
Between 0.594 inches and 0.656 inches
Body Length:
1.031 inches
Mounting Lip Diameter:
Between 1.9950 inches and 2.0050 inches
Mounting Lip Depth:
Between 0.0880 inches and 0.0980 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 7200.0 and 7201.0
Maximum Starting Torque:
2.00 inch-ounces
Maximum Running Torque:
1.40 inch-ounces
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:

Clamp ring

## NSN 5905-00-856-1585

Precision Wire Wound Variable Resistor - Page 2 of 2



Features Provided:
Nonmetallic shaft
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
7375.0 and 7385.0
Function Conformity Tolerance Per Section:
-0.01/+0.01 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
80.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-300.0/+300.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A002a0