

View Online at <https://aerobasegroup.com/nsn/5905-00-856-6157>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.156 inches

Shaft Diameter:

Between 0.248 inches and 0.250 inches

Body Length:

0.625 inches

Overall Diameter:

1.484 inches

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

312.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Stop Torque:

192.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.526 inches and 0.536 inches

Mechanical Backlash In Deg Angular Rotation:

1.500

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Nonmetallic shaft

Rotary Actuator Travel In Angular Deg:

312.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.25 heat sink single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0