

View Online at <https://aerobasegroup.com/nsn/5905-00-858-6691>

Section Quantity:

3

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 1.5610 inches and 1.5620 inches

Pilot Length:

Between 0.0570 inches and 0.0670 inches

Overall Length:

2.986 inches

Undercut Diameter:

Between 1.561 inches and 1.562 inches

Undercut Width:

Between 0.0680 inches and 0.0780 inches

Body Diameter:

1.750 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.500 inches

Body Length:

1.986 inches

Mounting Lip Diameter:

Between 1.7400 inches and 1.7500 inches

Mounting Lip Depth:

Between 0.0570 inches and 0.0670 inches

Shaft Style:

Round

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

25.0 percent, rated amperes c and better select

Rotary Actuator Travel In Angular Deg:

360.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 all sections

Power Dissipation Rating Per Section In Watts:

4.5 free air all sections

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 all sections

Actuator Travel Control Feature:

Continuous motion

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0