

View Online at <https://aerobasegroup.com/nsn/5905-00-858-8704>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

2.688 inches

**Body Diameter:**

1.062 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

1.688 inches

**Mounting Bushing Length:**

0.313 inches

**Body Length:**

1.000 inches

**Overall Diameter:**

1.438 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

320.0

**Maximum Starting Torque:**

10.00 inch-ounces

**Maximum Running Torque:**

4.00 inch-ounces

**Nonturn Device Location:**

At 12 oclock

**Nonturn Device Radius:**

0.375 inches

**Shaft End Play:**

0.005 inches

**Shaft Runout:**

0.002 inches

**Lateral Runout:**

0.002 inches

**Pilot Diameter Runout:**

0.001 inches

**Shaft Radial Play:**

0.002 inches

**Mechanical Backlash In Deg Angular Rotation:**

1.0

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing w/shaft seal

**Electrical Resistance Per Section:**

5.0 percent, rated amperes c and better industrial clears

**Rotary Actuator Travel In Angular Deg:**

330.0

**Function Conformity Tolerance Per Section:**

-2.00/+2.00 all sections

**Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 all sections

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-100.0/+100.0 all sections

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Function Conformity Per Section:**

All sections stepped conformity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 1st section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

All sections table

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 all sections

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Test Data Document:**

29173-561c15 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

6 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0