

View Online at <https://aerobasegroup.com/nsn/5905-00-859-2933>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.8740 inches and 0.8750 inches

Pilot Length:

0.0620 inches

Overall Length:

2.010 inches

Undercut Diameter:

Between 0.874 inches and 0.875 inches

Undercut Width:

Between 0.0630 inches and 0.0730 inches

Body Diameter:

1.000 inches

Shaft Diameter:

Between 0.249 inches and 0.250 inches

Shaft Length:

0.437 inches

Body Length:

1.573 inches

Mounting Lip Diameter:

1.0000 inches

Mounting Lip Depth:

Between 0.0570 inches and 0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 3600.0 and 3604.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.40 inch-ounces

Maximum Stop Torque:

50.00 inch-ounces

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.88 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 3600.0 and 3604.0

Function Conformity Tolerance Per Section:

-0.05/+0.05 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Power Dissipation Rating Per Section In Watts:

3.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-3.0/+3.0 single section

Actuator Travel Control Feature:

Clutch

Function Characteristic Per Section:

Single section 360 degrees sine

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0