NSN 5905-00-860-7706

Section Quantity:

175.0 single section

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-860-7706

1
Body Style:
Rectangular
Reliability Indicator:
Not established
Overall Length:
0.547 inches
Terminal Length:
0.187 inches
Overall Height:
Between 0.307 inches and 0.317 inches
Overall Width:
Between 0.240 inches and 0.260 inches
Body Length:
Between 0.360 inches and 0.380 inches
Body Width:
Between 0.220 inches and 0.240 inches
Body Height:
Between 0.312 inches and 0.317 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
280.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Stop Torque:
8.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.180 inches and 0.220 inches
Terminal Location:
Right adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
10.000 ohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.090 inches and 0.110 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

NSN 5905-00-860-7706

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Nο