

View Online at <https://aerobasegroup.com/nsn/5905-00-861-7650>

**Section Quantity:**

1

**Body Style:**

Cylindrical hole/slot mounted

**Reliability Indicator:**

Not established

**Overall Length:**

4.375 inches

**First Flat Length:**

1.562 inches

**Flat Height:**

0.344 inches

**Body Diameter:**

6.000 inches

**Shaft Diameter:**

0.375 inches

**Shaft Length:**

2.000 inches

**Body Length:**

2.375 inches

**Overall Diameter:**

6.438 inches

**Mounting Hole/stud Circle Diameter:**

2.376 inches

**Shaft Style:**

Round, flatted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

320.0

**Fragility Factor:**

Moderately rugged

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unc

**Screw Thready Qty Per Inch (tpi):**

20.0

**Mounting Facility Quantity:**

2

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Threaded hole

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

160.0 ohms c and better flooring

**Rotary Actuator Travel In Angular Deg:**

320.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

340.0 single section

**Power Dissipation Rating Per Section In Watts:**

300.0 7th secondary quality

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0