Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-861-7650

Section Quantity:

1

Body Style:

Cylindrical hole/slot mounted

Reliability Indicator:

Not established

Overall Length:

4.375 inches

First Flat Length:

1.562 inches

Flat Height:

0.344 inches

Body Diameter:

6.000 inches

Shaft Diameter:

0.375 inches

Shaft Length:

2.000 inches

Body Length:

2.375 inches

Overall Diameter:

6.438 inches

Mounting Hole/stud Circle Diameter:

2.376 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

20.0

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference



Mounting Method: Threaded hole **Features Provided:** Humidity proof **Electrical Resistance Per Section:** 160.0 ohms c and better flooring **Rotary Actuator Travel In Angular Deg:** 320.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section **Power Dissipation Rating Per Section In Watts:** 300.0 7th secondary quality **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0