

View Online at <https://aerobasegroup.com/nsn/5905-00-862-6532>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.581 inches

Body Diameter:

1.750 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.536 inches

Mounting Bushing Length:

0.350 inches

Body Length:

0.800 inches

Overall Diameter:

1.984 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Double ended shaft

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Shaft End Play:

0.005 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.0015 inches

Shaft Radial Play:

0.001 inches

Screw Thread Diameter:

0.138 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

32.0

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring and threaded hole

Electrical Resistance Per Section:

20.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

328.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Power Dissipation Rating Per Section In Watts:

3.5 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0