Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-862-9335

# Section Quantity:

2

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## First Flat Length:

0.344 inches

#### Flat Height:

0.215 inches

Body Diameter:

1.562 inches

## Shaft Diameter:

0.250 inches

## Shaft Length:

Between 0.844 inches and 0.906 inches

## Mounting Bushing Length:

0.375 inches

**Body Length:** 

3.500 inches

## Shaft Style:

Round, flatted

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

300.0

#### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

## Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

64.0 ohms all sections

# Rotary Actuator Travel In Angular Deg:

300.0

# Power Dissipation Rating Per Section In Watts:

25.0 free air all sections



**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 all sections

# Actuator Travel Control Feature:

Stops

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

## Fiig:

A002a0