NSN 5905-00-863-5590

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-863-5590 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0670 inches **Undercut Diameter:** 1.870 inches **Undercut Width:** 0.0550 inches **Body Diameter:** 2.005 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Body Length:** 1.050 inches **Mounting Lip Diameter:** 2.0050 inches **Mounting Lip Depth:** 0.0550 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Shaft Runout:** 0.001 inches **Lateral Runout:**

Pilot Diameter Runout:

0.002 inches

0.001 inches

NSN 5905-00-863-5590

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-400.0/+400.0 single section
Power Dissipation Rating Per Section In Watts:
4.0 free air single section
Function Conformity Per Section:
Single section absolute conformity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-20.0/+0.0 ohms single section
Resistance Tolerance Per Section In Percent:
-20.0/+0.0 single section
Actuator Travel Control Feature:
Continuous motion
Tap Location From Ccw Terminal Per Section In Ohms:
250.0 single section
Function Characteristic Per Section:
Single section graph
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Special Features:
0.033 in. Diameter through hole 0.156 in. From shaft end
Test Data Document:
19200-1054539 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
4 turret
Shelf Life:

-

N/a

Unit Of Measure:

NSN 5905-00-863-5590

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0