NSN 5905-00-864-0636

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-864-0636 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.718 inches **Body Diameter:** 1.062 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 1.093 inches **Overall Diameter:** 1.093 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Radially positioned over less than half the circumference

Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location: Mounting Method:** Locking bushing **Electrical Resistance Per Section:** 50.0 ohms all sections **Power Dissipation Rating Per Section In Watts:** 2.0 free air all sections

NSN 5905-00-864-0636

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent	Resistance	Tolerance	Per	Section	ln	Percent:
---	------------	------------------	-----	---------	----	----------

-10.0/+10.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0