Nonprecision Wire Wound Variable Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-864-2283

;	Section Quantity:
	1
ļ	Reliability Indicator:
ļ	Not established
;	Shaft Diameter:
(	0.250 inches
;	Shaft Length:
(	0.875 inches
;	Shaft Style:
I	Round, slotted
4	Actuator Type:
;	Single shaft
I	Nonturn Device Location:
,	At 12 oclock
I	Nonturn Device Radius:
(	0.500 inches
;	Screw Thread Diameter:
(	0.375 inches
;	Screw Thread Series Designator:
l	Unef
;	Screw Thready Qty Per Inch (tpi):
;	32.0
I	Mounting Method:
;	Standard bushing
I	Electrical Resistance Per Section:
ą	8.0 kilohms single section
I	Power Dissipation Rating Per Section In Watts
ļ	50.0 free air single section
I	Resistance Tolerance Per Section In Percent:
	-10.0/+10.0 single section
;	Standard Taper Curve Per Section:
,	A single section
•	Terminal Type And Quantity:
	3 tab, solder lug
	Shelf Life:
	N/a
ļ	Unit Of Measure:
I	Demilitarization:
I	No
	Fiig:
	A002a0